



PRO8TM UPGRADE

"Building the best, servicing the rest"TM



DESIGN FEATURES & BENEFITS

- 0.7mm thickness - reduced bending and increased durability
- Bright annealed finish - allows for better evaluation of CIP response
- Improved inlet design - ideal for viscous products
- Enlarged hanger - allows plates to slide smoothly during installation or inspection
- Snap-in Gasket - provides secure gasket attachment

AGC ADVANTAGES

- Pro8 has existing AGC ProFlow design features & improved thermal performance
- For new AGC frames and upgrade for Clip8, Front8 and C8 frames without piping changes
- Plates packed in order per streaming diagram
- In stock and ready to ship - minimal lead time
- Onsite installation service available



PRO8™

AGC Pro8™
enlarged hanger
design

Old style hanger
offers little clearance

AGC Pro8™ ENLARGED HANGER
allows plates to slide smoothly
during installation or inspection




SNAP-IN GASKET
provides secure
gasket attachment

Old style restricted
inlet design

AGC Pro8™
free-flow
inlet design

AGC Pro8™ ENLARGED OPENING
provides lower pressure drop in
the port inlet



METAL TO METAL ALIGNMENT
device and reinforced side band

ASK ABOUT OUR PRO8™ TIE-BOLT AND TWIN SPINDLE AUTO CLOSE FRAMES!

GENERAL INFORMATION

Plate and Gasket Weight:	Stainless Steel 5.9lbs / 2.68kg Hastelloy 5.8 lbs / 2.63 kg
Heat Transfer Area:	4.1ft ² / 0.38m ²
Plate Thickness:	0.7mm Stainless Steel 0.6mm Hastelloy
Volume (per channel):	0.38 gallons / 1.4L
Gasket Options:	Nitrile (NBR), EPDM



Western

9109 SE 64th Ave.
Portland, OR 97206
+1.503.774.7342
+1.800.715.8820
FAX +1.503.774.2550

Central

8400 Lakeview Parkway
Suite 700
Pleasant Prairie, WI 53158
+1.847.301.6890
+1.888.489.8820

Eastern

10129 Piper Lane
Bristow, VA 20136
+1.703.257.1660
+1.800.825.8820
FAX +1.703.330.7940

proflow sanitary
S E R I E S

See us on the web at www.agcheattransfer.com