

PRO10 UPDGRADE



DESIGN FEATURES & BENEFITS

- + 0.7mm thickness reduced bending and increased durability
- Bright annealed finish allows for better evaluation of CIP response
- + Improved inlet design ideal for viscous products
- Enlarged hanger allows plates to slide smoothly during installation or inspection
- + Snap-in gasket provides secure gasket attachment

AGC ADVANTAGES

- + Prol0[™] has existing AGC ProFlow design features & improved thermal performance
- For new AGC frames and upgrade for Clip10, Front10 and C10 frames without piping changes
- + Plates packed in order per streaming diagram
- + In stock and ready to ship minimal lead time
- + Onsite installation service available

BUILDING THE BEST. SERVICING THE REST.



WESTERN

3109 NE 230th Avenue Fairview, OR 97024 +1.503.774.7342 +1.800.715.8820 FAX +1.503.774.2550

MIDWEST

8400 Lakeview Parkway Suite 700 Pleasant Prairie, WI 53158 +1.847.301.6890 +1.888.489.8820

EASTERN

10129 Piper Lane Bristow, VA 20136 +1.703.257.1660 +1.800.825.8820 FAX +1.703.330.7940

PRO10™




AGC Pro10™ enlarged hanger allows plates to slide smoothly during installation or inspection

Snap-in gasket provides secure gasket attachment





AGC Pro10™ enlarged opening provides lower pressure drop in the port inlet



device and reinforced side band

ASK ABOUT OUR PRO10™ TIE-BOLT AND TWIN SPINDLE AUTO CLOSE FRAMES!

GENERAL INFORMATION

Plate & Gasket Weight Stainless Steel 9.74 lbs /4.42kg Hastelloy 8.41 lbs / 3.81 kg

Heat Transfer Area 6.67 ft²/.62m²

Plate Thickness 0.7mm Stainless Steel 0.6mm Hastelloy

Volume (per channel) 0.64 gallons / 2.4L

Gasket Options Nitrile (NBR), EPDM





